

Project:


Tik-Tak LED Chandelier Spec Sheet


SKU: 2802.03

LED rods are suspended in tandem pairs on multiple levels, perpendicular to each other. Each rod can be independently positioned as up or down light, and adjusted with infinite variability to any height along the suspension cables. Dramatic in the precision of their orientation and range of verticality, Tik-Tak brings a crisp presence to the volume of space.

Learn more: https://sonnemanlight.com/tik-tak-led-chandelier

Type #:





Dimensions

| Height: 0.75" | Width: 47.5" | Length: 47.5" | Size: Stack 2-Tier | Canopy/Backplate/Base Width: 7.75" | Canopy/Backplate/Base Depth: 7.75" | Canopy/Backplate/Base Height: 1"

Electrical Specs

Bulb(s) Included?: Bulb 1 Type: Bulb Quantity: Integral LED Input Voltage: 100-277VAC Wattage: Initial Lumens: 41 4550 **Delivered Lumens:** 2500 Kelvin: 3000K CRI: 90 Power Supply Type: Driver Power Supply Quantity: Power Supply Location: 1 Remote Dimming Type: Bulb Max Wattage: TRIAC/ELV/0-10V

Installation

Installation: Licensed electrician required Sloped Ceiling Compatible?: Compatible up to 45° Minimum Hanging Height: 4.25" Maximum Hanging Height: 121.5"

Shipping

 Carton 1 L x W x H:
 67" X 11" X 7"

 Carton 1 Gross Weight:
 9 LBS

Shade

Shade Material: Optical Acrylic

General Listings

Certification: C-ETL-US
Color/Finish: Satin White (.03)

Available Finishes

Available Finishes: Polished Chrome (.01), Satin Black (.25), Satin Nickel (.13), Satin White (.03)

Available Color Temperatures

Available Color Temperatures: 3000k

Options In This Family

sku	Size	Wattage	CRI	Delivered Lumens
2801.XX	Tandem	20	90	1250
2802.XX	Stack 2-Tier	41	90	2500
2803.XX	Stack 3-Tier	61	90	3750
2804.XX	Stack 4-Tier	82	90	5000
2805.XX	Stack 5-Tier	102	90	6250
2806.XX	Stack 6-Tier	123	90	7500