

### Project:

# Offset LED Surface Mount Spec Sheet


**SKU**: 2729.98

Two plates held in tandem, their unified geometry combines ambient illumination with a powerful downlight. Now available in rectangular and racetrack form factors in multiple lengths.

 $Learn\ more:\ \underline{https://sonnemanlight.com/offset-led-surface-mount}$ 

#### Type #:





### **Dimensions**

 Height:
 2.5"

 Width:
 15"

 Length:
 15"

 Diameter:
 15.75"

 Canopy/Backplate/Base:
 10"

 Shape:
 800

 Size:
 16"

## **Electrical Specs**

 Bulb(s) Included?:
 Yes

 Bulb 1 Type:
 Integral LED

 Input Voltage:
 120-277VAC

 Wattage:
 30

 Initial Lumens:
 2700

 Delivered Lumens:
 1918

 Kelvin:
 3000K

 CRI:
 90

 Power Supply Type:
 Driver

 Power Supply Quantity:
 1

 Power Supply Location:
 Canopy

 Dimming Type:
 TRIAC & ELV @ 120V / 0-10V

 Bulb Max Wattage:
 30

### Installation

Installation: Licensed electrician required

### Shipping

 Carton 1 L x W x H:
 19" X 19" X 6"

 Carton 1 Gross Weight:
 9 LBS

#### Shade

Shade Material: Aluminum Shade 2 Material: Acrylic Acrylic

## **General Listings**

 Features:
 At NYDC

 Certification:
 C-ETL-US

 Color/Finish:
 Textured White (.98)

 Dark Sky Friendly:
 N

## Available Finishes

Available Finishes: Textured White (.98)

## **Available Color Temperatures**

Available Color Temperatures: 3000k